

)	
SCWI160808TL-1N6	1.6	250	18	250	0.040	12500	700
SCWI160808TL-1N8	1.8	250	16	250	0.045	12500	700
SCWI160808TL-2N2	2.2	250	12	250	0.090	10000	700
SCWI160808TL-3N3	3.3	250	20	250	0.075	5900	700
SCWI160808TL-3N6	3.6	250	22	250	0.075	5900	700
SCWI160808TL-3N9	3.9	250	22	250	0.080	6900	700
SCWI160808TL-4N3	4.3	250	22	250	0.075	5900	700
SCWI160808TL-4N7	4.7	250	20	250	0.116	5800	700
SCWI160808TL-5N1	5.1	250	20	250	0.120	5700	700
SCWI160808TL-5N6	5.6	250	18	250	0.200	5700	700
SCWI160808TL-6N8	6.8	250	27	250	0.110	5800	700
SCWI160808TL-7N5	7.5	250	28	250	0.110	4800	700
SCWI160808TL-8N2	8.2	250	28	250	0.120	4700	700
SCWI160808TL-9N5	9.5	250	26	250	0.150	5400	700
SCWI160808TL-10N	10.0	250	31	250	0.130	4800	700
SCWI160808TL-12N	12.0	250	35	250	0.130	4000	700
SCWI160808TL-15N	15.0	250	30	250	0.150	4000	700
SCWI160808TL-18N	18.0	250	35	250	0.170	3100	700
SCWI160808TL-22N	22.0	250	38	250	0.190	3000	700
SCWI160808TL-27N	27.0	250	36	250	0.220	2800	600
SCWI160808TL-33N	33.0	250	36	250	0.220	2300	600
SCWI160808TL-36N	36.0	250	36	250	0.250	2080	600
SCWI160808TL-39N	39.0	250	40	250	0.250	2200	600
SCWI160808TL-43N	43.0	250	36	250	0.280	2000	600
SCWI160808TL-47N	47.0	200	36	200	0.280	2000	600
SCWI160808TL-56N	56.0	200	38	200	0.280	1900	600
SCWI160808TL-68N	68.0	200	36	200	0.340	1700	600
SCWI160808TL-75N	75.0	150	30	150	0.600	1400	400
SCWI160808TL-82N	82.0	150	34	150	0.550	1700	400
SCWI160808TL-R10	100.0	150	30	150	0.630	1400	400
SCWI160808TL-R12	120.0	150	32	150	0.730	1300	300
SCWI160808TL-R15	150.0	150	28	150	0.800	990	280
SCWI160808TL-R18	180.0	100	25	100	1.450	990	240
SCWI160808TL-R20	200.0	100	25	100	1.550	900	200
SCWI160808TL-R22	220.0	100	25	100	2.100	900	200
SCWI160808TL-R27	270.0	100	24	100	2.300	900	170
SCWI160808TL-R33	330.0	100	25	100	3.890	900	100
SCWI160808TL-R39	390.0	100	25	100	4.350	800	100

Note: When ordering, please specify tolerance code. Tolerance: J=±5%, K=±10%, M=±20%

